



INTERIOR
EXTERIOR



DEKS OLJE® D.2

HIGH GLOSS OIL VARNISH

<p>Product description</p>	<p>DEKS OLJE® D.2 is a varnish like, tough, flexible and durable finish that enhances the natural beauty of the wood. Easy to maintain and apply the more coats of DEKS OLJE® D.2 applied the higher the gloss finish. Unlike traditional varnishes DEKS OLJE® D.2 will not craze or blister and because of DEKS OLJE® D.1*'s penetrating qualities will not peel or flake as water is unable to get in to the wood.</p>
<p>Properties</p>	<p>Flexible film that does not craze, peel or flake. High gloss finish. Highly transparent varnish – enhances the natural beauty of the wood. Long term protection. No sanding between coats. Easy maintenance. Easy repair, no stripping.</p>
<p>Basic uses</p>	<p>Hardwoods and Exotic hardwoods - Teak, Ipe, Mahogany, Iroko, Bangkirai... New or weathered wood. Exterior use - Rubbing Strakes, Handrails, Wheel houses, booms, masts... Interior use - Furniture, Seating... Horizontal & Vertical.</p>
<p>Technical data</p>	<p>Finish: Gloss. Vehicle Type: Alkyd-Urethane Resins. Solvent Type: Solvent. Viscosity: Semi-Fluid. Specific Gravity: 0,910 ± 0,05 (68°F - 20°C). Physical State: Liquid. Solid Content: 56 % ± 5. Flammability: Not classified as flammable. Flash point: > 140°F (60°C). Shelf Life: 2 years in original unopened packaging. Container Size: 1L (1.06 U.S QUART), 2.5L (0.66 U.S. GALLON), 20L (5.28 U.S. GALLON). Color: Amber. Dry time: 12-24 hours, depending on temperature and humidity. Re-coating Time: 12 hours. Setting up Time Before Use: 3 days. VOC: Does not exceed 399 g/l (3.32 lb/gal).</p>
<p>Application tools</p>	<p>Brush, Roller.</p>
<p>Good application practice</p>	<p>Cover everything you do not wish to paint. Apply between 46°F (8°C) and 95°F (35°C). Do not apply in direct sunlight or on to hot surfaces.</p>

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

Surface preparation	<p>New wood:</p> <ul style="list-style-type: none"> All new wood must be treated with DEKS OLJE® D.1* as per label directions. <p>Weathered wood previously treated with DEKS OLJE® D.1*:</p> <ul style="list-style-type: none"> Surfaces must be clean, dry and free of all surface contamination. If DEKS OLJE® D.1* has lightened to a light gray finish, clean and restore as per label and technical data directions before applying DEKS OLJE® D.2. <p>Wood already treated with DEKS OLJE® D.2:</p> <ul style="list-style-type: none"> See maintenance.
Application	<ul style="list-style-type: none"> DO NOT THIN. USE AS IS. Apply 6 coats of DEKS OLJE® D.2 allowing a minimum of 12 hours between coats. All coats should be applied within 1 month. Sanding between coats is not required. For an extra high gloss finish, sand between the last 2 coats with 600 grit paper . Allow 3 days for DEKS OLJE® D.2 to set-up and dry, before putting the boat in service.
Coverage	161 ft ² (15 m ²) per liter.
Maintenance	<p>Wash frequently with fresh water to remove salt and dirt.</p> <p>Areas worn back to DEKS OLJE® D.1* treated wood:</p> <p>Sand with 320 grit paper.</p> <p>Clean worn area with DECK CLEANER* as per label directions. Leave to dry.</p> <p>Top up DEKS OLJE® D.1* as per label directions.</p> <p>Apply required number of DEKS OLJE® D.2 coats to bring up to level of existing finish.</p> <p>Rough or Abraded areas:</p> <p>Wet sand surface using 320 grit paper and DEKS OLJE® D.1* as the lubricant.</p> <p>Wipe over with a clean, dry, lint free cloth and leave to dry 24 hours.</p> <p>Apply 2 coats of DEKS OLJE® D.2.</p> <p>New full coat:</p> <p>Wet sand the whole surface using 320 grit paper and DEKS OLJE® D.1* as the lubricant.</p> <p>Wipe over with a clean, dry, lint free cloth and leave to dry 24 hours.</p> <p>Apply 1 or 2 coats of DEKS OLJE® D.2 as desired.</p>
Restrictions	<p>DEKS OLJE® D.2 should only be applied to surfaces treated with DEKS OLJE® D.1* or previously finished with DEKS OLJE® D.2.</p> <p>Do not apply DEKS OLJE® D.2 in wet weather or late in the day when dew or fog may be expected. This may dull a newly set film causing it to blush - exposure to sunlight usually removes the discoloration.</p> <p>DEKS OLJE® D.2 is very slippery, especially when wet and we therefore do not recommend the use of it on decks and other areas where it will be walked on.</p>
Clean-up	<p>Clean all tools and equipment with mineral spirits while still wet. If allowed to dry, remove with paint stripper. Wipe up any drips or runs immediately with a cloth soaked in mineral spirits. Dried DEKS OLJE® D.2 may be removed with MARINE STRIP*.</p> <p>Store and maintain equipment as directed by manufacturer.</p> <p>NOTE: Any rags, steel wool etc soaked in DEKS OLJE® D.2 may spontaneously catch fire if improperly discarded. Rags, steel wool etc must be saturated with water after use or placed in a sealed, water filled metal container, before disposing with household waste.</p>
Storage	<ul style="list-style-type: none"> Left over DEKS OLJE® D.2 should be transferred to a smaller, airtight, closed metal or glass container. Keep from freezing and high temperature.
General information	<p>Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL INTERNATIONAL is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advise and information please contact us on contact@deksolje.com.au.</p> <p>The information above is correct at the date of issue.</p>
Safety	<p>Keep out of the reach of children.</p> <p>MSDS available at www.deksolje.com.au</p>
Issue date	December 2015.

* Same manufacturer

